

COB LED STRIP



Specifications



Model No.	UK-COB-400-IP20-1-24-5mm	Lumen (Lm)	850-1000Lm
LED Type	COB	Cutting Unit	20mm(24V)
LED Qty(pcs/m)	400 pcs/m	Adhesive Tape	3M 9495LE 300MP
IC	/	PCB Type/Color	2 oz , White PCB
Pixel Qty(pcs/m)	/	Dimension:	5000*5mm
Color	6500K/4000K/3000K	Package	5m/bag
CCT	/	Max Run Length	5m
Ra	>90	IP Grade	IP20
Work Voltage	24V DC	Warranty	3 Years
Peak Power (w/m)	10W/M	Certification	UL CE RoHS
Power Per Roll (5 meters)	50W	Ta	-25~40°C ; Tc : 75°C (max)
SDCM	3 Step		

Remark : data with 15% tolerance

Typical Color

6500K	
4000K	
3000K	

CCT Available:

Packing Information

Standard Packing Per Bag

5 meters/reel, 1 reel/anti-static bag
G.W. : Non-waterproof-0.6KG

Standard Packing Per Outer Carton

outer carton size: 48*29*24cm 100rolls 500 m
G.W of Carton: 6.8 kg
Volume of Carton: 0.034 m³

Remark : data with 10% tolerance

Precautions

- *Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- *Do not fold it in case any damage of LED beads.
- *Risk of electric shock, installation MUST be operated by a well-qualified electrician, if the LED strip is damaged, the product must
- *Make sure the supply voltage meets the requirements and the circuit is installed correctly before power supply.
- *Make sure the electric connection reliable and be well protected.
- *Cut off the power before operating the product.
- *Forbidden to use in water.

NOTES

1. LED-S LED Strip maintains a tester tolerance of $\pm 5\%$ on Color Temperature and Lumen , tolerance of ± 3 on CRI-Ra
2. The test is based on the LED-S's laboratory and testing equipment.
3. We reserve the right to modify and improve the design of our fixtures without prior notice.

LED-S

<https://led-svet.com.ua>

info@led-svet.com.ua