

COB LED STRIP



Specifications



Model No.	XR-COB-320-IP20-8-24	Lumen (Lm)	850Lm
LED Type	COB	Cutting Unit	50mm(24V)
LED Qty(pcs/m)	320 pcs/m	Adhesive Tape	3M 9495LE 300MP
IC	/	PCB Type/Color	2 oz , White PCB
Pixel Qty(pcs/m)	/	Dimension:	5000*8mm
Color	6500K/4000K/3000K	Package	5m/bag
CCT	/	Max Run Length	5m
Ra	>90	IP Grade	IP20/IP54/WP/TWPJ
Work Voltage	24V DC	Warranty	3 Years
Peak Power (w/m)	8W	Certification	UL CE RoHS
Power Per Roll (5 meters)	40W	Ta	-25~40°C ; Tc : 75°C (max)
SDCM	3 Step		

Remark : data with 15% tolerance

Typical Color

6500K	
4000K	
3000K	
Customize	

NOTES: More customized colors, please contact our sales .

CCT Available :

Packing Information

Standard Packing Per Bag

5 meters/reel, 1 reel/anti-static bag

G.W. : Non-waterproof-0.09KG

Standard Packing Per Outer Carton

outer carton size: 61*36*20cm 100rolls 500 m

G.W of Carton: 10.7 kg

Volume of Carton: 0.044 m³

Remark : data with 10% tolerance

Precautions

*Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.

*Do not fold it in case any damage of LED beads.

*Risk of electric shock, installation MUST be operated by a well-qualified electrician, if the LED strip is damaged, the product must

*Make sure the supply voltage meets the requirements and the circuit is installed correctly before power supply.

*Make sure the electric connection reliable and be well protected.

*Cut off the power before operating the product.

*Forbidden to use in water.

NOTES

1. LED Strip maintains a tester tolerance of $\pm 5\%$ on Color Temperature and Lumen , tolerance of ± 3 on CRI-Ra
 2. The test is based on the laboratory and testing equipment.
 3. We reserve the right to modify and improve the design of our fixtures without prior notice.
-