

COB LED STRIP



Specifications



Model No.	XR-COB-576-IP20-RGB-15-24
LED Type	COB
LED Qty(pcs/m)	576 pcs/m
IC	/
Pixel Qty(pcs/m)	/
Color	/
CCT	RGB
Ra	/
Work Voltage	24V DC
Peak Power (w/m)	15W
Power Per Roll (5 meters)	75W
SDCM	/

Lumen (Lm)	520-550Lm
Cutting Unit	31mm(24V)
Adhesive Tape	3M 9495LE 300MP
PCB Type/Color	2 oz , White PCB
Dimension:	5000*10mm
Package	5m/bag
Max Run Length	5m
IP Grade	IP20/IP65/IP67
Warranty	3 Years
Certification	UL CE RoHS
Ta	-25~40°C ; Tc : 75°C (max)

Remark : data with 15% tolerance

Typical Color

RGB	

CCT Available:

Packing Information

Standard Packing Per Bag

5 meters/reel, 1 reel/anti-static bag

G.W. : Non-waterproof-0.120KG

Standard Packing Per Outer Carton

25 bags to 1 inner box, size : 33.5x20x24cm

4 inner boxes to 1 outer carton size: 42x35x46cm

G.W of Carton: 13KG

Volume of Carton: 0.068 m³

Remark : data with 10% tolerance

Precautions

*Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.

*Do not fold it in case any damage of LED beads.

*Risk of electric shock, installation MUST be operated by a well-qualified electrician, if the LED strip is damaged, the product must

*Make sure the supply voltage meets the requirements and the circuit is installed correctly before power supply.

*Make sure the electric connection reliable and be well protected.

*Cut off the power before operating the product.

*Forbidden to use in water.

NOTES

1. LED-S Strip maintains a tester tolerance of $\pm 5\%$ on Color Temperature and Lumen, tolerance of ± 3 on CRI-Ra

2. The test is based on the LED-D's laboratory and testing equipment.

3. We reserve the right to modify and improve the design of our fixtures without prior notice.

LED-S

<https://led-svet.com.ua>

info@led-svet.com.ua